



C7 / C35 Filament LED Lamps

Clear / Golden / Frosted / Milky

A++ Energy Class | ENERGY STAR | Life Time 20000 hrs | ErP | CE | UL | RoHS | REACH |



C7 Clear

EU VERSION (220-240V)

Wattage & Lumen :
0.4 W / 40 lm

US VERSION (110-130V)

Wattage & Lumen :
0.4 W / 40 lm

Size (mm) :

Ø22 X 58 (E12)
Ø22 X 61 (E14)

6500K / 4000K / 2700K

C35 Clear

EU VERSION (220-240V)

Wattage & Lumen :
2 W / 250 lm
4 W / 470 lm

2.5 W / 250 lm (Dimmable)
3.5 W / 350 lm (Dimmable)
4.5 W / 470 lm (Dimmable)

US VERSION (110-130V)

Wattage & Lumen :
1.6 W / 115 lm
2 W / 200 lm
4 W / 350 lm
5 W / 580 lm

2.5 W / 200 lm (Dimmable)
3.5 W / 350 lm (Dimmable)
4.5 W / 500 lm (Dimmable)

Size (mm) :
Ø35 X 91 (E26)
Ø35 X 92 (E27)
Ø35 X 91 (B22)

6500K / 4000K / 2700K

EU VERSION (220-240V)

Wattage & Lumen :
2 W / 250 lm
4 W / 470 lm

2.5 W / 250 lm (Dimmable)
3.5 W / 350 lm (Dimmable)
4.5 W / 470 lm (Dimmable)
5 W / 540lm(Dim)(Housing)

US VERSION (110-130V)

Wattage & Lumen :
1.6 W / 115 lm
2 W / 200 lm
4 W / 350 lm
2.5 W / 200 lm (Dimmable)

3.5 W / 350 lm (Dimmable)
4.5 W / 500 lm (Dimmable)

Size (mm) :
Ø35 X 99 (E12)
Ø35 X 100 (E14)
Ø35 X 97 (B15)

6500K / 4000K / 2700K

C35 Golden

EU VERSION (220-240V)

Wattage & Lumen :
2 W / 210 lm
4 W / 400 lm

2.5 W / 180 lm (Dimmable)
4.5 W / 400 lm (Dimmable)

US VERSION (110-130V)

Wattage & Lumen :
2 W / 210 lm
4 W / 400 lm

2.5 W / 200 lm (Dimmable)
3.5 W / 300 lm (Dimmable)
4.5 W / 350 lm (Dimmable)

Size (mm) :
Ø35 X 91 (E26)
Ø35 X 92 (E27)
Ø35 X 91 (B22)

2200K / 2400K / 2700K

EU VERSION (220-240V)

Wattage & Lumen :
2 W / 210 lm
4 W / 400 lm

2.5 W / 180 lm (Dimmable)
4.5 W / 350 lm (Dimmable)

US VERSION (110-130V)

Wattage & Lumen :
2 W / 210 lm
4 W / 420 lm

2.5 W / 200 lm (Dimmable)
3.5 W / 300 lm (Dimmable)
4.5 W / 350 lm (Dimmable)

Size (mm) :
Ø35 X 99 (E12)
Ø35 X 100 (E14)
Ø35 X 97 (B15)

2200K / 2400K / 2700K

C35 Frosted

EU VERSION (220-240V)

Wattage & Lumen :
2 W / 220 lm
4 W / 470 lm

US VERSION (110-130V)

Wattage & Lumen :
2.5 W / 200 lm (Dimmable)
3.5 W / 350 lm (Dimmable)

Size (mm) :
Ø35 X 92 (E27)
Ø35 X 91 (B22)

6500K / 4000K / 2700K

EU VERSION (220-240V)

Wattage & Lumen :
2 W / 220 lm
4 W / 470 lm

3.5 W / 320 lm (Dimmable)
4.5 W / 430 lm (Dimmable)

US VERSION (110-130V)

Wattage & Lumen :
2.5 W / 200 lm (Dimmable)
3.5 W / 350 lm (Dimmable)

Size (mm) :
Ø35 X 99 (E12)
Ø35 X 100 (E14)
Ø35 X 97 (B15)

6500K / 4000K / 2700K

C35 Milky

EU VERSION (220-240V)

Wattage & Lumen :
2 W / 220 lm
4.5 W / 420 lm (Dimmable)

US VERSION (110-130V)

Wattage & Lumen :
1.6 W / 105 lm
4 W / 300 lm (Dimmable)
4.5 W / 420 lm (Dimmable)
5.5 W / 500 lm (Dimmable)

Size (mm) :
Ø35 X 91 (E26)
Ø35 X 92 (E27)
Ø35 X 91 (B22)

6500K / 4000K / 2700K

EU VERSION (220-240V)

Wattage & Lumen :
2 W / 200 lm
2.5 W / 200 lm (Dimmable)
4.5 W / 400 lm (Dimmable)

US VERSION (110-130V)

Wattage & Lumen :
1.6 W / 105 lm
4 W / 300 lm (Dimmable)
5.5 W / 500 lm (Dimmable)

Size (mm) :
Ø35 X 99 (E12)
Ø35 X 100 (E14)
Ø35 X 97 (B15)

6500K / 4000K / 2700K

C35L Filament LED Lamps

Clear / Golden / Frosted / Milky

| A++ Energy Class | ENERGY STAR | Life Time 20000 hrs | ErP | CE | UL | RoHS | REACH |



C35L Clear

EU VERSION (220-240V)	EU VERSION (220-240V)
Wattage & Lumen :	Wattage & Lumen :
2 W / 250 lm	2 W / 250 lm
4 W / 470 lm	4 W / 470 lm
4.5 W / 470 lm (Dimmable)	4.5 W / 470 lm (Dimmable)
US VERSION (110-130V)	US VERSION (110-130V)
Wattage & Lumen :	Wattage & Lumen :
1.6 W / 115 lm	1.6 W / 115 lm
2 W / 250 lm	2 W / 250 lm
3 W / 350 lm	3 W / 350 lm
4 W / 470 lm	4 W / 470 lm
2.5 W / 250 lm (Dimmable)	2.5 W / 250 lm (Dimmable)
3.5 W / 350 lm (Dimmable)	3.5 W / 350 lm (Dimmable)
4.5 W / 500 lm (Dimmable)	4.5 W / 500 lm (Dimmable)
Size (mm) :	Size (mm) :
Ø35 X 111 (E26)	Ø35 X 119 (E12)
	Ø35 X 120 (E14)
	Ø35 X 118 (B15)
6500K / 4000K / 2700K	6500K / 4000K / 2700K



C35L Golden

EU VERSION (220-240V)	EU VERSION (220-240V)
Wattage & Lumen :	Wattage & Lumen :
4.5 W / 350 lm (Dimmable)	4.5 W / 350 lm (Dimmable)
US VERSION (110-130V)	US VERSION (110-130V)
Wattage & Lumen :	Wattage & Lumen :
2 W / 210 lm	2 W / 210 lm
4 W / 400 lm	4 W / 420 lm
3.5 W / 300 lm (Dimmable)	3.5 W / 300 lm (Dimmable)
4.5 W / 350 lm (Dimmable)	4.5 W / 350 lm (Dimmable)
Size (mm) :	Size (mm) :
Ø35 X 111 (E26)	Ø35 X 119 (E12)
	Ø35 X 120 (E14)
	Ø35 X 118 (B15)
2000K	2000K / 2400K



C35L Frosted

EU VERSION (220-240V)	EU VERSION (220-240V)
Wattage & Lumen :	Wattage & Lumen :
4 W / 470 lm	4.5 W / 470 lm (Dimmable)
US VERSION (110-130V)	US VERSION (110-130V)
Wattage & Lumen :	Wattage & Lumen :
3.5 W / 350 lm (Dimmable)	3.5 W / 350 lm (Dimmable)
4.5 W / 500 lm (Dimmable)	4.5 W / 500 lm (Dimmable)
Size (mm) :	Size (mm) :
Ø35 X 111 (E26)	Ø35 X 119 (E12)
	Ø35 X 120 (E14)
	Ø35 X 118 (B15)
6500K / 4000K / 2700K	6500K / 4000K / 2700K



C35L Milky

EU VERSION (220-240V)	EU VERSION (220-240V)
Wattage & Lumen :	Wattage & Lumen :
2 W / 220 lm	2 W / 220 lm
4 W / 420 lm	4 W / 420 lm
	4.5 W / 400 lm (Dimmable)
US VERSION (110-130V)	US VERSION (110-130V)
Wattage & Lumen :	Wattage & Lumen :
4 W / 300 lm (Dimmable)	4 W / 300 lm (Dimmable)
5.5 W / 500 lm (Dimmable)	
Size (mm) :	Size (mm) :
Ø35 X 112 (E27)	Ø35 X 120 (E14)
Ø35 X 111 (B22)	Ø35 X 118 (B15)
6500K / 4000K / 2700K	6500K / 4000K / 2700K

CT35 Filament LED Lamps

Clear / Golden / Milky

| A++ Energy Class | Life Time 20000 hrs | ErP | CE | RoHS | REACH |



CT35 Clear

EU VERSION (220-240V)	EU VERSION (220-240V)
Wattage & Lumen : 2 W / 250 lm 4 W / 470 lm 4.5 W / 470 lm (Dimmable)	Wattage & Lumen : 2 W / 250 lm 4 W / 470 lm 4.5 W / 470 lm (Dimmable)
Size (mm) : Ø35 X 92 (E27)	Size (mm) : Ø35 X 100 (E14)
6500K / 4000K / 2700K	6500K / 4000K / 2700K



CT35 Golden

EU VERSION (220-240V)	EU VERSION (220-240V)
Wattage & Lumen : 4.5 W / 400 lm (Dimmable)	Wattage & Lumen : 4.5 W / 350 lm (Dimmable)
Size (mm) : Ø35 X 92 (E27)	Size (mm) : Ø35 X 100 (E14)
2200K / 2400K / 2700K	2000K



CT35 Milky

EU VERSION (220-240V)	EU VERSION (220-240V)
Wattage & Lumen : 2 W / 220 lm 4 W / 420 lm 4.5 W / 420 lm (Dimmable)	Wattage & Lumen : 2 W / 220 lm 4 W / 420 lm 4.5 W / 400 lm (Dimmable)
Size (mm) : Ø35 X 92 (E27)	Size (mm) : Ø35 X 100 (E14)
6500K / 4000K / 2700K	6500K / 4000K / 2700K